

CH-D2160MIN 16CH Real Time Digital Video Recorder



Features:

- Real-time Live Display.
- CF Card Backup.
- Ethernet Function.
- Motion detection.
- Video Looping Output.
- 1-channel Audio Input/Output.
- Maximum 2 Hard Disks capability (One removable).
- Time lapse and real time recording.
- Records up to 60 PPS (pictures per second),
- Image quality selectable at 3 different levels for recording.
- Manual / Alarm recording mode.
- Disk-full warning and operation status LEDs.
- Password protection.
- RS-232 communication port.

SPECIFICATIONS

Item	CH-D2160MIN	Item	CH-D2160MIN
Video Input	BNC x 16	Playback Speed	Fast Forward/Reverse x2,x4,x6,x8 , Frame By Frame Playback
Display Rate	Up to 480 Frame/sec	Title	6 Characters
Video Looping	BNC x 16	OSD & Setup	Title/Time/Date/Setup Menu
Video Output	BNC x 1	Alarm Input	x16 NO or NC Programmable
Call Monitor Output	BNC x 1	Relay Output	NO or NC Programmable Contact x 1
Audio Input	RCA x 1	RS-232 Port	Yes
Audio Output	RCA x 1	Password Control	Yes
Image System	NTSC / PAL	Backup	CF Card(※Option)
Mode	Triplex	Ethernet	Yes
Resolution	Display:720x576, Record:720x288	Power Input	AC 100 ~ 240V Input (50/60 Hz)
Recording Rate	Up to 60 /50 fields/sec	Dimensions	430(W) x 380(D) x 88(H) mm
Storage Media	Max 2 IDE Hard Disks (One Removable)	Rack Mountable	EIA 19" 2U Standard Mounting Rack
Image Format	Wavelet	Internet	YES
Recording Mode	Manual / Alarm / Schedule		

TIME LAPSE RECORD TIME (80 GB Hard Disk)

FPS(field per second)		60/50	30/25	10	5	2	1	0.5	0.2
Record Quality	Best	8hr	16hr	48hr	96hr	240hr	480hr	960hr	2400hr
	High	12hr	24hr	72hr	144hr	360hr	720hr	1440hr	3600hr
	Medium	18hr	37hr	111hr	222hr	555hr	1110hr	2220hr	5550hr
	Low	22hr	44hr	132hr	264hr	660hr	1320hr	2640hr	6660hr