



CH-LCD104AV



CH-LCD140AV / CH-LCD150AV-1/2

Specification

Model	CH-LCD104AV	CH-LCD140AV	CH-LCD150AV-1	CH-LCD150AV-2
LCD Panel	10.4" TFT LCD	14" TFT LCD	15" TFT LCD	
Display Pixels	800 x 600	640 x 480	1024 x 768	
Active Area (mm)	211.2 x 158.4	283 x 212.4	304.1 x 228.1	
LCD Profile Ratio	4:3			
Display Colors	262K	16.2M	262K	
Brightness (nit)	400	450	250	350
Contrast Ratio	500:1	500:1	400:1	
Viewing Angle (U/D/L/R)	40 / 60 / 60 / 60	85 / 85 / 85 / 85	40 / 60 / 60 / 60	
Response Time	35ms	25ms	16ms	
Input Signal	Video: 2CH Composite video. 1.0 Vp-pt 75ohm S-Video: Y: 1.0 Vp-p w/Neg. SYNC. C:0.285 Vp-p PC: Analog RGB Audio: 2 CH L/R, 50 ~ 100 mVp-p.			
In/Out Impedance	75 ohm / Auto Terminal			
Operation System	NTSC / PAL / SVGA / VGA	NTSC / PAL / VGA	NTSC / PAL / XGA / SVGA / VGA	
Input/Output connector	Video: 2 CH BNC Input/Output Audio: 2 CH RCAR.L Input/Output PC: 15 Pin D-Sub connector S-Video: 4-Pin Min-DIN			
Power Source	90 ~ 260V AC 60Hz / 50 Hz Adaptor / DC 12V			
Power Consumption	1.1A / 13.2W	2.5A / 30W	1.5A / 18W	
Dimension(mm)(LxWxD)	266.2 x 213.3 x 56	368 x 295 x 80	385 x 310 x 80	
Weight/Net (Kg)	2.38	4.6	4.2	4
Bracket	VESA 100 Standard			
Operation Temperature	-10°C ~ 50°C / 14°F ~ 122°F			