

**FEATURES**

- Suitable for all kinds of advertisement
- 20-inch LCD-TV Level
- High Performance
- High Brightness of 500 cd/m²
- High Contrast at 500 : 1
- Fast Response Time of 16ms
- Best Viewing Angle
- NTSC / PAL / SECAM Auto Detect
- Multiplexer Video Input / Output Interface
- Easy OSD Menu User Interface
- 3D De-interlace
- 3D Comb filter
- VESA Standard Bracket

Specification

Model	CH-LCD201AV
LCD Panel	20" TFT LCD Monitor for Multi Media Advertisement
Front Panel	Power ON/OFF; OSD Control Function
Display Resolution	800 x 600 : 640 x 480 (PC), SVGA, VGA
Active Area (mm)	480 x 306
LCD Profile Ratio	4 : 3
LCD Panel Type	TN Mode, Normally White
Dot Pitch (mm)	0.51 x 0.51mm
Display Colors	16.7M (8 bit for R,G,B)
Brightness	500cd/m ² typ.
Contrast Ratio	450 : 1 typ.
Viewing Angle	L/R : 80° ; U/D : 60°
Power Source	90~260V AC 60Hz / 50Hz , Adapter or DC12V
Input Signal	Video: 0.5 to 2.0 Vp-p composite video, S-Video: Y:1.0Vp-p w/Neg. SYNC. C: 0.285Vp-p PC: Analog RGB
In/Output Impedance	75 ohms / Auto Terminal
Operation System	NTSC : 525 TV Lines ; PAL : 625 TV Lines
Input/Output Connector	Video: 2CH BNC Input/Output Audio: 2CH RCA R.L Input/Output PC: 15 Pin D-Sub connector S-Video: 4 Pin DIN connector
Power Consumption	55W
Dimension/Weight	490.5mm(W) x 388.5(L) x 66.8(H) / 7Kg
Bracket	VESA 100 Standard
Operation Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Certifications	UL 、 CE 、 FCC 、 BSMI 、 C-Tick