



CH-LCD56DH/DU



CH-LCD68D



CD-LCD70D

Specification

Model	CH-LCD56DH	CH-LCD56DU	CH-LCD68D	CD-LCD70D
LCD Panel	5.6" TFT LCD		6.8" TFT LCD	7.0" TFT LCD
Resolution	960 x 234		1150 x 234	1440 x 234
Brightness	250 cd/m ²	350 cd/m ²	300 cd/m ²	250 cd/m ²
Contrast Ratio	150 : 1			
View Angle	L/R : ±45° U/D : 10° / 30°		L/R : ±45° U/D : 10° / 30°	L/R : ±65° U/D : 35° / 60°
System	NTSC/PAL Switch able	NTSC/ PAL (Auto)		NTSC/PAL Switch able
Video Input	2 CH A / V Input / 1.0 Vp-p at 75Ω			
Audio Input	(MONO) 30m ~ 100m Vp-p			R/L 30m ~ 100m Vp-p
Video / Audio Connector	Min phone jack/Mini phone plug to RCA plug adapter			
User Control	Mode ◀ ▶ power OSD Controls			
Power Supply	DC12 ±10% (DC12-30V Option)			
Power Consumption	7.0W (max)		7.5W (max)	8.5W (max)
Operating Temperature	-10°C ~ 50°C / 14°F ~ 122°F			
Dimension (mm) (WxHxD)	160 x 133 x 37		172 x 144 x 30.7	191 x 130 x 39
Weight Net	468g		586g	590g