

HTA-810 Time & Attendance Recorder

Display	7-segment LED x 4 + Dual Color LED x 3
Magnetic card reader	ISO track1, track 2, track 3
Barcode reader	IR, numerical code 39 or code 128
RFID reader	ABA-Track2 / Wiegand 26 bit
Records capacity	8200
Supported interface	TCP/IP, RS-485, RS-232
Bell control relay	X 1
Power supply	DC 12 V, 600mA
Operating temperature	-10 °C ~ 55 °C / 14 °F ~ 131 °F
Operating Humidity	10% ~ 95%
Dimensions	160mm (L) x 100mm (W) x 40mm (H)
Weight	300g



RTA-600 Time Attendance Recorder



Bar code reader	Infra red slot reader: Resolution 0.15mm, Scanning speed: 100~1000mm/sec.
Magnetic strip reader	ISO Standard Track: T1, T2, T3
Proximity reader	ABA-Track 2
Input device	1 sensor
Output device	2 relay
Indicators	LCD display and 3 LED
Keypads	21 keys
Beep tone	Buzzer
Memory	64K ROM and 128K SRAM
Storage capacity	5000 events
Communication interface	RS-232, RS-422, RS-485
Operating voltage	DC 12V @ 1000mA
Power consumption	7W (max)
Baud rate	9600bps-N-8-1
Operating temperature	0 °C ~ 55 °C / 32 °F ~ 131 °F
Relative humidity	20% ~ 95% (Non condensing)
Dimensions	140mm (L) x 205mm (W) x 70mm (H)
Weight	800g